



## RAN Series Vane Type Rotary Actuators

This compact aluminum alloy body series is lightweight and provides easy mounting and installation. This series provides OEM customers flexibility for installation with 5 different mounting options available. Six different rotation degree specifications from 90° to 275°.

- Double Acting Single Vane Type
- Low Air Leakage and Long Life Operation
- Utilizes 4 mm Solid State Sensors

- Four Mounting Options for Easy Installation
- 90° to 275° Rotation Options
- RoHS Compliance

Improve the performance and reduce the size of your next generation machine. Koganei sets the standard for supplying innovative high-quality solutions with unmatched reliability. Optimized designs, with a wide variety of styles and sizes, increase speed to market as well as provide solutions for most applications. Expedite deliveries with product stocked in the USA.

KOGANEI is committed to your success from concept, to initial design, to final delivery and beyond.

Operations

Double Acting Vane

## RAN Series Vane Type Rotary Actuators

Click Here for Access to Catalogs, CAD Drawings, Videos and More!

Model	Operation	Bore mm	Rotation	Stroke	Port Size	Effective	Allowable	Allowable	Allowable	Allowable	Pressure	Temperature
			Angles	Adjustment	metric	Torque*	Energy	Radial Load	Thrust Load	Moment	Range	Range
			degrees	degrees	[imperial]	N [lbf]	J [ft.lbf]	N [lbf]	N [lbf]	Nm [ft.lbf]	MPa [psi]	°C [°F]
RAN	Double Acting Vane	1	90, 100, 180,	Not Adjustable	M5 x 0.8	0.118	0.0004	19.6	2	Consult Factory	0.25 - 0.7	5 - 60
			270		[upon request]	[0.087]	[0.004]	[4.41]	[0.45]		[36.3 - 101.5]	[41 - 140]
RAN	Double Acting Vane	3	90, 100, 180,	Not Adjustable	M5 x 0.8	0.294	0.002	39.6	3.9	Consult Factory	0.2 - 0.7	5 - 60
			270		[upon request]	[0.217]	[0.018]	[8.9]	[0.877]		[29.0 - 101.5]	[41 - 140]
RAN	Double Acting Vane	8	90, 100, 180,	Not Adjustable	M5 x 0.8	0.785	0.005	58.8	5.9	Consult Factory	0.2 - 0.7	5 - 60
			270		[upon request]	[0.579]	[0.044]	[13.22]	[1.326]		[29.0 - 101.5]	[41 - 140]
RAN	Double Acting Vane	20	90, 100, 180,	Not Adjustable	M5 x 0.8	1.961	0.015	294.2	29.4	Consult Factory	0.2 - 0.7	5 - 60
			270		[upon request]	[1.446]	[0.133]	[66.14]	[6.609]		[29.0 - 101.5]	[41 - 140]
RAN	Double Acting Vane	50	90, 100, 180,	Not Adjustable	Rc 1/8	5.197	0.06	588.4	98.1	Consult Factory	0.2 - 0.7	5 - 60
			190, 275		[upon request]	[3.833]	[0.531]	[132.28]	[22.054]		[29.0 - 101.5]	[41 - 140]

\* @ 0.5 MPa / 72.5 psi