



050 / H050 Series - Direct Acting Solenoid Valves for Vacuum

This series offers most compact in size double solenoid valve configuration from KOGANEI available with LED indicators. The Selection Guide provides a summary of the 2 different 050 / H050 Series - Direct Acting Solenoid Valves for Vacuum.

- Lead Wire or DIN Connector
- Poppet Design Allows for Fast Response with Minimal Leakage
- FKM Seal Option
- Direct Acting, Inline Single or Double Solenoid
- Cleanroom Option
- RoHS Compliance

Improve the performance and reduce the size of your next generation machine. Koganei sets the standard for supplying innovative high-quality solutions with unmatched reliability. Optimized designs, with a wide variety of styles and sizes, increase speed to market as well as provide solutions for most applications. Expedite deliveries with product stocked in the USA.

KOGANEI is committed to your success from concept, to initial design, to final delivery and beyond.

Operations

2/2, 3/2 Single Low Current Vacuum

2/2, 3/2 Single Vacuum

050 / H050 Series - Direct Acting Solenoid Valves for Vacuum

[Click Here for Access to Catalogs, CAD Drawings, Videos and More!](#)

Model	Operation	Valve Width mm [in]	Flow Rate Cv	Orifice Size mm [in]	Port Sizes metric [imperial]	Mounting	Piping	Voltages	Power Consumption W	Max Frequency Hz	Pressure Range MPa [psi]	Temperature Range °C [°F]
V050LE1 / V050LE1-F11	2/2, 3/2 Single Low Current Vacuum	27 [1.06]	0.08	1.5 [0.059]	M5 x 0.8 [10-32 UNF]	Inline, Block Manifold	Direct	24 DC 100, 200 AC	2.4 - 2.7	5	-0.1 - 0.9 [-14.5 - 130.5]	0 - 50 [32 - 122]
V050E1 / V050E1-F11	2/2, 3/2 Single Vacuum	27 [1.06]	0.08	1.5 [0.059]	M5 x 0.8 [10-32 UNF]	Inline, Block Manifold	Direct	24 DC 100, 200 AC	5.8 - 9.2	5	-0.1 - 0.9 [-14.5 - 130.5]	0 - 50 [32 - 122]