



## K Series - High Speed Direct Acting Solenoid Valves for Vacuum

The world's fastest direct acting valve series with a cycle rate up to 500Hz in a 10mm width body. The Selection Guide provides a summary of the 6 different K Series - High Speed Direct Acting Solenoid Valves for Vacuum.

- High-speed Response
- Power Saving Circuit Option
- Surge Suppression Circuit
- IP67 Protection Rating
- Non-oil Specification
- RoHS Compliance

Improve the performance and reduce the size of your next generation machine. Koganei sets the standard for supplying innovative high-quality solutions with unmatched reliability. Optimized designs, with a wide variety of styles and sizes, increase speed to market as well as provide solutions for most applications. Expedite deliveries with product stocked in the USA.

KOGANEI is committed to your success from concept, to initial design, to final delivery and beyond.

### Operations

3/2 Single Vacuum & Standard Flow Base

3/2 Single Vacuum & Standard Flow Direct

## K Series - High Speed Direct Acting Solenoid Valves for Vacuum

[Click Here for Access to Catalogs, CAD Drawings, Videos and More!](#)

Model	Operation	Valve Width mm [in]	Flow Rate Cv	Orifice Size mm [in]	Port Sizes metric [imperial]	Mounting	Piping	Voltages	Power Consumption W	Max Frequency Hz	Pressure Range MPa [psi]	Temperature Range °C [°F]
K3-100VA-04	3/2 Single Vacuum & Standard Flow Base	10 [0.39]	0.06	1 [0.039]	4 mm, 6 mm, M5 x 0.8 [upon request]	Single Subbase	Base	24 DC	4 - 4.1	50	-0.1 - 0.7 [-14.5 - 101.5]	0 - 50 [32 - 122]
K3-100VA-02	3/2 Single Vacuum & Standard Flow Base	10 [0.39]	0.06	1 [0.039]	4 mm, 6 mm, M5 x 0.8 [upon request]	Single Subbase	Base	24 DC	2 - 2.2	50	-0.1 - 0.7 [-14.5 - 101.5]	0 - 50 [32 - 122]
K3-100VA-24	3/2 Single Vacuum & Standard Flow Base	10 [0.39]	0.08	1.5 [0.059]	4 mm, 6 mm, M5 x 0.8 [upon request]	Single Subbase	Base	24 DC	2 - 24	100	-0.1 - 0.7 [-14.5 - 101.5]	0 - 50 [32 - 122]
K3-100VF-04	3/2 Single Vacuum & Standard Flow Direct	10 [0.39]	0.06	1 [0.039]	4 mm, 6 mm, M5 x 0.8 [upon request]	Inline	Direct	24 DC	4 - 4.1	50	-0.1 - 0.7 [-14.5 - 101.5]	0 - 50 [32 - 122]
K3-100VF-02	3/2 Single Vacuum & Standard Flow Direct	10 [0.39]	0.06	1 [0.039]	4 mm, 6 mm, M5 x 0.8 [upon request]	Inline	Direct	24 DC	2 - 2.2	50	-0.1 - 0.7 [-14.5 - 101.5]	0 - 50 [32 - 122]
K3-100VF-24	3/2 Single Vacuum & Standard Flow Direct	10 [0.39]	0.08	1.5 [0.059]	4 mm, 6 mm, M5 x 0.8 [upon request]	Inline	Direct	24 DC	2 - 24	100	-0.1 - 0.7 [-14.5 - 101.5]	0 - 50 [32 - 122]

Focused on providing industry leading pneumatic, fluid handling, and electrical automation components and assemblies for the OEM market | Think KOGANEI