



KKF Series - Activated Charcoal Filters

These filters removes odors and oil vapors in work processes over long period of time. The Selection Guide provides a summary of the 2 different Activated Charcoal Filters.

- Eliminates Odors with Active Charcoal Element
- Standard Auto Drain
- Durable Construction

- Filter Monitoring Differential Pressure Ports Standard
- Long Service Life Element Due to Large Surface Area Design
- RoHS Compliance

Improve the performance and reduce the size of your next generation machine. Koganei sets the standard for supplying innovative high-quality solutions with unmatched reliability. Optimized designs, with a wide variety of styles and sizes, increase speed to market as well as provide solutions for most applications. Expedite deliveries with product stocked in the USA.

KOGANEI is committed to your success from concept, to initial design, to final delivery and beyond.

Operations

Activated Charcoal Filter

KKF Series - Activated Charcoal Filters

Click Here for Access to Catalogs, CAD Drawings, Videos and More!

		Office for Floodess to Outdings, one Brainings, Floodes and more.													
	Model	Operation	Port Sizes metric	Width mm [in]	Modular	Max Flow I/m [cfm]	Filtration micron	Bowl Volume	Bowl Drain Types	Set Pressure Range	Relief Start Pressure	Gauge Port Sizes metric	Operating Pressure	Temperature Range	
			[imperial]					ml [oz]		MPa [psi]	MPa [psi]	[imperial]	MPa [psi]	°C [°F]	
	KKF-150	Activated Charcoal Filter	Rc1/2 [upon request]	90 [3.54]	No	1000 [35.3]	N/A	N/A	None	N/A	N/A	N/A	0.05 - 0.97 [7.3 - 140.7]	5 - 60 [41 - 140]	
	KKF-200	Activated Charcoal Filter	Rc3/4 [upon request]	115 [4.53]	No	1650 [58.3]	N/A	N/A	None	N/A	N/A	N/A	0.05 - 0.97 [7.3 - 140.7]	5 - 60 [41 - 140]	