



## MBDA Cleanroom Series - Mini Bit Cylinders

For the most compact square body actuator available at only 4.5 mm bore, these miniature actuators help OEM customers do more in less space.

- Class 10 / ISO 4 Equivalent Cleanroom Models
- Plain or Male Thread Piston Rod
- RoHS Compliance

- Short Mounting Pitch
- ZE Solid State Sensor Switch Optional

Improve the performance and reduce the size of your next generation machine. Koganei sets the standard for supplying innovative high-quality solutions with unmatched reliability. Optimized designs, with a wide variety of styles and sizes, increase speed to market as well as provide solutions for most applications. Expedite deliveries with product stocked in the USA.

KOGANEI is committed to your success from concept, to initial design, to final delivery and beyond.

Operations

Double Acting Clean System

## MBDA Cleanroom Series - Mini Bit Cylinders

Click Here for Access to Catalogs, CAD Drawings, Videos and More!

Model	Operation	Bore mm	Standard Strokes	Max Stroke	Port Size	Max Force - Push	Max Force - Pull	Speed Range	Pressure Range	Temperature Range
			mm	mm	metric	N	N	mm/s	MPa	°C
			[in]	[in]	[imperial]	[lbf]	[lbf]	[in/s]	[psi]	[°F]
CS-MBDA	Double Acting Clean System	4.5	4 - 10	10	M3 x 0.5	11.1	9	50 - 500	0.15 - 0.7	0 - 60
			[upon request]	[0.4]	[upon request]	[2.5]	[2]	[2.0 - 19.7]	[21.8 - 101.5]	[32 - 140]
CS-MBDA	Double Acting Clean System	6	4 - 15	15	M3 x 0.5	19.7	14.8	50 - 500	0.15 - 0.7	0 - 60
			[upon request]	[0.6]	[upon request]	[4.4]	[3.3]	[2.0 - 19.7]	[21.8 - 101.5]	[32 - 140]
CS-MBDA	Double Acting Clean System	8	4 - 20	20	M3 x 0.5	35.2	30.2	50 - 500	0.15 - 0.7	0 - 60
			[upon request]	[0.8]	[upon request]	[7.9]	[6.8]	[2.0 - 19.7]	[21.8 - 101.5]	[32 - 140]
CS-MBDA	Double Acting Clean System	10	4 - 20	20	M3 x 0.5	55	46.1	50 - 500	0.1 - 0.7	0 - 60
			[upon request]	[0.8]	[upon request]	[12.4]	[10.4]	[2.0 - 19.7]	[14.5 - 101.5]	[32 - 140]