



## MRV Cleanroom Series - Magnet Type Flat Rodless Linear Actuators

This innovative, oval tube design magnetically coupled rodless cylinder provides the smallest height dimension, low center of gravity and inherent non-rotation.

- Non-guided, Oval Bore Magnetic Coupled Type
- Low Profile Design Allows Easy Integration with External Guides
- Superior Low and High Speed Range from 8 mm/s to 800 mm/s
- Oval Bore Design Provides Non-rotating Operation
- Optional Integrated Patented Linear Orifice Shock Absorbers
- RoHS Compliance

Improve the performance and reduce the size of your next generation machine. Koganei sets the standard for supplying innovative high-quality solutions with unmatched reliability. Optimized designs, with a wide variety of styles and sizes, increase speed to market as well as provide solutions for most applications. Expedite deliveries with product stocked in the USA.

KOGANEI is committed to your success from concept, to initial design, to final delivery and beyond.

### Operations

Double Acting Clean System

Double Acting with Shock Absorber Clean System

## MRV Cleanroom Series - Magnet Type Flat Rodless Linear Actuators

[Click Here for Access to Catalogs, CAD Drawings, Videos and More!](#)

Model	Operation	Bore mm	Standard Strokes mm [in]	Max Stroke mm [in]	Port Size metric [imperial]	Max Force - Push N [lbf]	Max Force - Pull N [lbf]	Speed Range mm/s [in/s]	Pressure Range MPa [psi]	Temperature Range °C [°F]
CS-MRV	Double Acting Clean System	14	100 - 500 [upon request]	1000 [39.4]	M5 x 0.8 [upon request]	110 [25]	110 [25]	8 - 500 [0.3 - 19.7]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRV	Double Acting Clean System	22	200 - 800 [upon request]	1500 [59.1]	M5 x 0.8 [upon request]	241 [54]	241 [54]	8 - 500 [0.3 - 19.7]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRV	Double Acting Clean System	28	200 - 800 [upon request]	1500 [59.1]	Rc 1/8 [upon request]	440 [99]	440 [99]	8 - 500 [0.3 - 19.7]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRV	Double Acting Clean System	35	200 - 1000 [upon request]	2000 [78.7]	Rc 1/8 [upon request]	687 [154]	687 [154]	8 - 500 [0.3 - 19.7]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRV	Double Acting Clean System	45	200 - 1000 [upon request]	2000 [78.7]	Rc 1/8 [upon request]	1,126 [253]	1,126 [253]	8 - 500 [0.3 - 19.7]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRV	Double Acting Clean System	56	200 - 1000 [upon request]	2000 [78.7]	Rc 1/4 [upon request]	1,758 [395]	1,758 [395]	8 - 500 [0.3 - 19.7]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]

Focused on providing industry leading pneumatic, fluid handling, and electrical automation components and assemblies for the OEM market | Think KOGANEI

### MRV Cleanroom Series - Magnet Type Flat Rodless Linear Actuators

[Click Here for Access to Catalogs, CAD Drawings, Videos and More!](#)

Model	Operation	Bore mm	Standard Strokes mm [in]	Max Stroke mm [in]	Port Size metric [imperial]	Max Force - Push N [lbf]	Max Force - Pull N [lbf]	Speed Range mm/s [in/s]	Pressure Range MPa [psi]	Temperature Range °C [°F]
CS-MRVZ	Double Acting with Shock Absorber Clean System	14	100 - 500 [upon request]	1000 [39.4]	M5 x 0.8 [upon request]	110 [25]	110 [25]	8 - 800 [0.3 - 31.5]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRVZ	Double Acting with Shock Absorber Clean System	22	200 - 800 [upon request]	1500 [59.1]	M5 x 0.8 [upon request]	241 [54]	241 [54]	8 - 800 [0.3 - 31.5]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRVZ	Double Acting with Shock Absorber Clean System	28	200 - 800 [upon request]	1500 [59.1]	Rc 1/8 [upon request]	440 [99]	440 [99]	8 - 800 [0.3 - 31.5]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRVZ	Double Acting with Shock Absorber Clean System	35	200 - 1000 [upon request]	2000 [78.7]	Rc 1/8 [upon request]	687 [154]	687 [154]	8 - 800 [0.3 - 31.5]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRVZ	Double Acting with Shock Absorber Clean System	45	200 - 1000 [upon request]	2000 [78.7]	Rc 1/8 [upon request]	1,126 [253]	1,126 [253]	8 - 800 [0.3 - 31.5]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]
CS-MRVZ	Double Acting with Shock Absorber Clean System	56	200 - 1000 [upon request]	2000 [78.7]	Rc 1/4 [upon request]	1,758 [395]	1,758 [395]	8 - 800 [0.3 - 31.5]	0.2 - 0.7 [29.0 - 101.5]	0 - 60 [32 - 140]